



**Pursuit of
Perfection
Environmental
Purity.**



Meer productinformatie:

info@energytools.nl

010-8439068

www.energytools.nl



Aeon Lighting Technology Inc.

High Power LED Lighting Solutions

www.aeonlighting.com

2011 ver 3

ALTLED®





reddot design award
winner 2011



BR30 (PAR30)
E26 / 24 (US)



Beam Angle : 25° / 38° / 120° Beam Angle : 60° / 72°





Working Voltage 100 - 240V AC
Weight 9.2 oz. (260 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 40.000+ hours
Warranty 2 Years Limited

BR30 (PAR30)
E26 / 27 (EURO)




Beam Angle : 25° / 38° / 120° Beam Angle : 60° / 72°



Working Voltage 100 - 240V AC
Weight 9.2 oz. (260 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 40.000+ hours
Warranty 2 Years Limited

Beam Angle





Color





CHIPSET LUMINAIRE

All lumen data from chipset manufacturers.



Chipsets			
Power Consumption		10 Watts	15 Watts
Beam Angle		120°	72° / 120°
True White	CRI 80	720 lm	1000 lm
Natural White	CRI 80	720 lm	1000 lm
Warm White	CRI 80	460 lm	650 lm





Chipsets				
Power Consumption		10 Watts	15 Watts	15 Watts
Beam Angle		25°	38°	72° / 120°
True White	CRI 80	780 lm	1800 lm	1000 lm
Natural White	CRI 80	680 lm	1475 lm	1000 lm
Warm White	CRI 80	630 lm	1300 lm	650 lm



Chipsets			
Power Consumption		10 Watts	15 Watts
Beam Angle		60° / 72° / 120°	
True White	CRI 65	680 lm	960 lm
Natural White	CRI 80	520 lm	740 lm
Warm White	CRI 82	450 lm	700 lm




Power Consumption		10 Watts	12 Watts	15 Watts
Beam Angle		60° / 72° / 120°		
True White	CRI 70	620 lm	700 lm	800 lm
	CRI 90	500 lm	-	640 lm
Natural White	CRI 70	510 lm	700 lm	650 lm
	CRI 90	410 lm	-	520 lm
Warm White	CRI 70	410 lm	560 lm	520 lm
	CRI 90	330 lm	-	420 lm




BR40 (PAR38)
E26 / 24 (US)



Beam Angle : 120°



Beam Angle : 60° / 72°




Working Voltage 100 - 240V AC
Weight 15.2 oz. (430 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 40,000+ hours
Warranty 2 Years Limited


BR40 (PAR38)
E26 / 27 (EURO)



Beam Angle : 120°



Beam Angle : 60° / 72°



Working Voltage 100 - 240V AC
Weight 15.2 oz. (430 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 40,000+ hours
Warranty 2 Years Limited

COMPATIBLE WITH E39/E40 SOCKET



BEAM ANGLE



COLOR



True White Natural White Warm White





CHIPSET LUMINAIRE

All lumen data from chipset manufacturers.



Chipsets	BRIDGELUX
Power Consumption	35 Watts
Beam Angle	60° / 72° / 120°
True White	CRI 65 2600 lm
Warm White	CRI 82 1560 lm



Chipsets	BRIDGELUX
Power Consumption	20 Watts
Beam Angle	60° / 72° / 120°
True White	CRI 65 1320 lm
Natural White	CRI 80 980 lm
Warm White	CRI 82 900 lm



Power Consumption	20 Watts
Beam Angle	60° / 72° / 120°
True White	CRI 70 1100 lm
	CRI 90 880 lm
Natural White	CRI 70 900 lm
	CRI 90 720 lm
Warm White	CRI 70 740 lm
	CRI 90 600 lm



Power Consumption	15 Watts
Beam Angle	60° / 72° / 120°
True White	CRI 70 800 lm
	CRI 90 640 lm
Natural White	CRI 70 650 lm
	CRI 90 520lm
Warm White	CRI 70 520 lm
	CRI 90 420 lm

